B-RADBATTERY SERIES



Each B-RAD Battery Series Tool Includes:

- Reaction arm and retaining ring
- Charger and two 18V batteries
- Weatherproof storage case
- Calibrated to ISO 17025 standards
- Safety instructions on USB Flash Drive
- Operators Manua





B-RAD BL SELECT

NEW! Torque ranges up to 5000 ft. lbs.

The newly designed B-RAD BL Select Series offers higher speed and longer battery life while incorporating a new torque display with buttons. The B-RAD BL Select allows the user to easily select the target torque. Patented Product.

- Now with digital torque settings, able to increase or decrease the value by 10 ft. lbs.
- Torque ranges up to 5000 ft. lbs.
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available
- Longer battery life as energy is used more efficiently



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	(ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENS I ON D
28283	B-RAD BL SELECT 500	0.75"	130	500	21.5	7.7	9.1"	2.5"	2.65"	10.3"
28285	B-RAD BL SELECT 1000	0.75"	200	1000	10.5	7.8	9.1"	2.5"	2.65"	10.3"
28286	B-RAD BL SELECT 1000-2	0.75"	200	1000	71	9.4	11"	2.5"	2.65"	10.3"
28287	B-RAD BL SELECT 1500	1.0"	300	1500	6	8.9	9.6"	2.7"	2.7"	10.3"
28288	B-RAD BL SELECT 1500-2	1.0"	300	1500	19.5	10.7	11.75"	2.7"	2.7"	10.3"
28289	B-RAD BL SELECT 3000	1.0"	600	3000	3	13.3	11.2"	3.2"	3.2"	10.5"
28290	B-RAD BL SELECT 3000-2	1.0"	600	3000	20	14.7	13.25"	3.2"	3.2"	10.5"
28291	B-RAD BL SELECT 5000	1.5"	1000	5000	2.1	19.3	11.6"	3.75"	3.75"	10.7"

B-RAD BL SELECT OFFSET

NEW! Offset gearboxes for tight spaces.

The newly designed B-RAD BL Select Offset Series offers more flexability for those tight spaces. With higher speed and longer battery life while incorporating a new torque display with buttons. The B-RAD BL Select Offset allows the user to easily select the target torque. Patented Product.

- Now with digital torque settings, able to increase or decrease the value by 10 ft. lbs.
- Torque ranges up to 5000 ft. lbs.
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available
- Longer battery life as energy is used more efficiently



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	(ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	DIMENSION E	DIMENSION F
30002	B-RAD BL SELECT 500 OFFSET	0.75"	130	500	21.5	8.7	10.2"	6.1"	2.5"	10.3"	3.3"	3.3"
29572	B-RAD BL SELECT 1000 OFFSET	0.75"	200	1000	10.5	8.8	10.3"	6.1"	2.5"	10.3"	3.3"	3.3"
30004	B-RAD BL SELECT 1500 OFFSET	1.0"	300	1500	6	9.9	10.9"	6.8"	2.7"	10.3"	3.4"	3.3"
30006	B-RAD BL SELECT 3000 OFFSET	1.0"	600	3000	3	14.3	12.3"	8.2"	3.2"	10.3"	3.6"	3.3"
30008	B-RAD BL SELECT 5000 OFFSET	1.5"	1000	5000	2.1	20.3	13.2"	9.1″	3.7"	10.3"	3.9"	3.3"

B-RAD BL S

The highest accuracy on the market.

The newest addition to the B-RAD series is the B-RAD BL S. Equipped with a built-in transducer, the B-RAD BL S makes torquing and logging easier and more efficient than ever with its ability to read and display torque in real time. With torque and angle capabilities, the B-RAD BL S is ready for the most critical applications and will hold up to scrutiny on a variety of projects. The B-RAD BL S includes Bluetooth connectivity, torque check functionality, and automatic reaction arm release to minimize your downtime and maximize your torque output.

• Torque range up to 5,000 ft. lbs.

New and improved battery life

• Bolt counter

Brushless motor

Password protection





PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	(ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
31800	B-RAD BL 500 S	0.75"	50	500	21	9.2	85	12.25"	2.48"	2.75"	10"
31802	B-RAD BL 1000 S	0.75"	100	1000	9.6	9.4	85	12.25"	2.48"	2.75"	10"
31804	B-RAD BL 1500 S	1.0"	150	1500	5.6	10.8	85	12.63"	2.7"	2.75"	10"
31806	B-RAD BL 3000 S	1.0"	300	3000	3	15.9	85	13.25"	3.18"	3.18"	10.13"
31808	B-RAD BL 5000 S	1.5"	500	5000	1.9	21.7	85	14.25"	3.74"	3.74"	10.5"

16 RAD TORQUE SYSTEMS

Accuracy of +/-5%, Repeatability of +/-2%

DIGITAL B-RAD

Ideal for applications where compressed air is not available! Up to 2 times faster than previous version!

Digital B-RAD powered torque wrenches are the world's first digital, cordless, and lithium-ion battery tool on the market. With advanced patented technology containing digital display and single increment torque settings.

- Available with torque and angle option
- Programmable preset torque settings
- Latest lithium-ion 18V battery technology
- High accuracy of +/-5%
- Automatic 2-speed gearbox
- Patented Product





PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	(ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
21779	DB-RAD 500-2	0.75"	50	500	59	11	80 db	12.67"	2.5"	2.5"	10.25"
21783	DB-RAD 1000-2	0.75"	100	1000	19	11.6	80 db	13"	2.5"	2.5"	10.25"
21787	DB-RAD 1500-2	1.0"	150	1500	17	11.8	80 db	13"	2.7"	2.7"	10.50"
24965	DB-RAD 3000-2	1.0"	300	3000	13	19.5	80 db	15.2"	3.2"	3.2"	10.5"